

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name INTEROX® 60-10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Uses of the Substance/Mixture

- Bleaching agents
- Chemical industry
- Electronic industry
- Metal treatment
- Odour agents
- Oxidizing agents
- Textile industry
- Manufacture of pulp, paper and paper products

1.3 Details of the supplier of the safety data sheet

Company

SOLVAY CHEMICALS INTERNATIONAL SA
RUE DE RANSBEEK, 310
1120, BRUXELLES
BELGIUM
Tel: +32-2-2642111
Fax: +32-2-2641802

PEROXIDOS DO BRASIL Ltda
RUA JOAO LUNARDELLI, 1301 - CIC
81460-100, CURITIBA
BRAZIL
Tel: +55-41-33165200
Fax: +55-41-33165201

E-mail address

manager.sds@solvay.com

1.4 Emergency telephone number

+44(0)1235 239 671 [CareChem 24]

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification (UN)

Oxidizing liquids, Category 2	H272: May intensify fire; oxidizer.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation. (Respiratory system)
Acute aquatic toxicity, Category 2	H401: Toxic to aquatic life.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

GHS label elements (UN)**Hazardous products which must be listed on the label**

- CAS-No. 7722-84-1 hydrogen peroxide

Pictogram**Signal word**

- Danger

Hazard statements

- H272 May intensify fire; oxidizer.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H335 May cause respiratory irritation.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statementsGeneral

- None

Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220 Keep away from clothing and other combustible materials.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

- P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
- P363 Wash contaminated clothing before reuse.
- P370 + P378 In case of fire: Use water spray to extinguish.

Storage

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

Disposal

- P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients**3.1 Substance**

- Not applicable, this product is a mixture.

3.2 Mixture

- Formula H_2O_2

Information on Components and Impurities

Chemical name	CAS-No.	GHS Classification	Concentration [%]
hydrogen peroxide	CAS-No. : 7722-84-1	Oxidizing liquids, Category 1 ; H271 Acute toxicity, Category 4 ; H302 Skin corrosion, Category 1A ; H314 Serious eye damage, Category 1 ; H318 Specific target organ toxicity - single exposure, Category 3 ; H335 Acute aquatic toxicity, Category 2 ; H401 Chronic aquatic toxicity, Category 3 ; H412 Specific concentration limit: C: >= 70 %, Oxidizing liquids, Category 1; H271 C: 50 - < 70 %, Oxidizing liquids, Category 2; H272 C: >= 70 %, Skin corrosion, Category 1A; H314 C: 50 - < 70 %, Skin corrosion, Category 1B; H314 C: 35 - < 50 %, Skin irritation, Category 2; H315 C: 8 - < 50 %, Serious eye damage, Category 1; H318 C: 5 - < 8 %, Eye irritation, Category 2; H319 C: >= 35 %, Specific target organ toxicity - single exposure, Category 3; H335 C: >= 63 %, Chronic aquatic toxicity, Category 3; H412 C: >= 63 %, Chronic aquatic toxicity, Category 4; Not classified	60

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

- Show this safety data sheet to the doctor in attendance.

In case of inhalation

- Move to fresh air.
- Oxygen or artificial respiration if needed.
- Victim to lie down in the recovery position, cover and keep him warm.
- Call a physician immediately.

In case of skin contact

- Take off contaminated clothing and shoes immediately.
- Wash off immediately with plenty of water.
- Keep warm and in a quiet place.
- Call a physician or poison control centre immediately.
- Wash contaminated clothing before re-use.

In case of eye contact

- Call a physician or poison control centre immediately.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- In the case of difficulty of opening the lids, administer an analgesic eye wash (oxybuprocaine).
- Take victim immediately to hospital.

In case of ingestion

- Call a physician or poison control centre immediately.
- Take victim immediately to hospital.
- If swallowed, rinse mouth with water (only if the person is conscious).
- Do NOT induce vomiting.
- Artificial respiration and/or oxygen may be necessary.

- If victim is conscious:
 - If swallowed, rinse mouth with water (only if the person is conscious).
 - Do NOT induce vomiting.

- If victim is unconscious:
 - Artificial respiration and/or oxygen may be necessary.

4.2 Most important symptoms and effects, both acute and delayed**In case of inhalation****Symptoms**

- Breathing difficulties
- Cough
- pulmonary oedema
- Nausea
- Vomiting

Effects

- Corrosive to respiratory system.

Repeated or prolonged exposure

- Nose bleeding
- Risk of chronic bronchitis

In case of skin contact**Symptoms**

- Redness
- Swelling of tissue

Effects

- Corrosive
- Causes severe burns.

In case of eye contact**Symptoms**

- Redness
- Lachrymation
- Swelling of tissue

Effects

- Corrosive
- Causes severe burns.
- Small amounts splashed into eyes can cause irreversible tissue damage and blindness.

In case of ingestion**Symptoms**

- Nausea
- Abdominal pain
- Bloody vomiting
- Diarrhoea
- Suffocation
- Cough
- Severe shortness of breath

Effects

- If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.
- Risk of respiratory disorder

4.3 Indication of any immediate medical attention and special treatment needed**Notes to physician**

- Take victim immediately to hospital.
- Immediate medical attention is required.
- Consult with an ophthalmologist immediately in all cases.
- Burns must be treated by a physician.
- If swallowed
- Avoid gastric lavage (risk of perforation).
- Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

- Water
- Water spray

Unsuitable extinguishing media

- None

5.2 Special hazards arising from the substance or mixture

- Oxidizing
- Decomposition will cause oxygen release which may intensify fire
- Oxygen
- Sustains combustion
- Contact with combustible material may cause fire.
- Contact with flammables may cause fire or explosions.
- Risk of explosion if heated under confinement.

5.3 Advice for firefighters**Special protective equipment for firefighters**

- In the event of fire, wear self-contained breathing apparatus.
- Use personal protective equipment.

- Wear chemical resistant oversuit

Further information

- Keep product and empty container away from heat and sources of ignition.
- Keep containers and surroundings cool with water spray.
- Approach from upwind.
- Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****Advice for non-emergency personnel**

- Prevent further leakage or spillage if safe to do so.
- Keep away from incompatible products

Advice for emergency responders

- Evacuate personnel to safe areas.
- Keep people away from and upwind of spill/leak.
- Use personal protective equipment.
- Drying of this product on clothing or combustible materials may cause fire.
- Keep wetted with water.

6.2 Environmental precautions

- Should not be released into the environment.
- If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

- Dilute with plenty of water.
- Dam up.
- Do not mix waste streams during collection.
- Soak up with inert absorbent material.
- Keep in properly labelled containers.
- Keep in suitable, closed containers for disposal.
- Treat recovered material as described in the section "Disposal considerations".

6.4 Reference to other sections

- Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Use only in well-ventilated areas.
- Before all operations, passivate the piping circuits and vessels according to the procedure recommended by the producer.
- Use only clean and dry utensils.
- Never return unused material to storage receptacle.
- Keep away from heat.
- Avoid inhalation, ingestion and contact with skin and eyes.
- Keep away from incompatible products

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

- Keep only in the original container.
- Store in a well-ventilated place. Keep cool.
- Store in a receptacle equipped with a vent.
- Keep in properly labelled containers.
- Keep container closed.
- Keep in a banded area.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Regularly check the condition and temperature of the containers.
- Keep away from:
- Incompatible products

Packaging material**Suitable material**

- aluminium 99,5 %
- stainless steel 304L / 316L
- Approved grades of HDPE.

7.3 Specific end use(s)

- Contact your supplier for additional information

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Components with other occupational exposure limits**

Components	Value type	Value	Basis
Hydrogen peroxide	TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls**Control measures****Engineering measures**

- Provide adequate ventilation.
- Apply technical measures to comply with the occupational exposure limits.

Individual protection measures**Respiratory protection**

- Use respirator when performing operations involving potential exposure to vapour of the product.
- When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Respirator with a vapour filter (EN 141)
- Self-contained breathing apparatus in case of: 1) large uncontrolled emissions, 2) insufficient oxygen, 3) the mask and cartridge do not give adequate protection.
- Recommended Filter type: ABEK-P2

Hand protection

- Impervious gloves

- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Suitable material

- PVC
- Natural Rubber
- butyl-rubber
- Nitrile rubber

Eye protection

- Chemical resistant goggles must be worn.
- If splashes are likely to occur, wear:
 - Tightly fitting safety goggles
 - Face-shield

Skin and body protection

- Impervious clothing
- If splashes are likely to occur, wear:
 - Chemical resistant apron
 - Boots
 - Suitable material
 - PVC
 - Natural Rubber

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

- Dispose of rinse water in accordance with local and national regulations.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

<u>Appearance</u>	Physical state: liquid Colour: colourless
<u>Odour</u>	odourless
<u>Odour Threshold</u>	No data available
<u>Molecular weight</u>	34 g/mol
<u>pH</u>	2.0 (21 °C) H ₂ O ₂ 50 % pKa: 11.6 (25 °C)
<u>Melting point/freezing point</u>	Freezing point: -0.43 °C Pure substance : -40.3 °C H ₂ O ₂ 70 %

<u>Initial boiling point and boiling range</u>	Boiling point/boiling range: 150.2 °C Pure substance 125 °C H2O2 70 %
<u>Flash point</u>	Not applicable
<u>Evaporation rate (Butylacetate = 1)</u>	No data available
<u>Flammability (solid, gas)</u>	Not applicable
<u>Flammability (liquids)</u>	The product is not flammable.
<u>Flammability/Explosive limit</u>	<u>Explosiveness:</u> Not explosive With certain materials (see section 10).
<u>Auto-ignition temperature</u>	The product is not flammable.
<u>Vapour pressure</u>	2 hPa (30 °C) H2O2 70 % 2.14 hPa (20 °C) Pure substance
<u>Vapour density</u>	1.02
<u>Density</u>	<u>Bulk density:</u> Not applicable
<u>Relative density</u>	1.29 H2O2 70 %
<u>Relative density</u>	1.44 (25 °C) Pure substance
<u>Solubility</u>	<u>Water solubility:</u> soluble
<u>Partition coefficient: n-octanol/water</u>	log Pow: -1.57 Method: Calculation method
<u>Decomposition temperature</u>	>= 60 °C Self-Accelerating decomposition temperature (SADT)
<u>Decomposition temperature</u>	< 60 °C Slow decomposition
<u>Viscosity</u>	<u>Viscosity, dynamic :</u> 1.26 mPa.s (20 °C) H2O2 70 % 1.249 mPa.s (20 °C) Pure substance
<u>Explosive properties</u>	No data available
<u>Oxidizing properties</u>	No data available

9.2 Other information

Henry's Constant	0.00075 Pa.m ³ /mol (20 °C) not significant, Air, Volatility
Surface tension	77.2 mN/m (20 °C) H ₂ O ₂ 70 % 80.4 mN/m (20 °C) Pure substance

SECTION 10: Stability and reactivity**10.1 Reactivity**

- Strong oxidizer. Contact with other material may cause fire.
- Decomposes on heating with potential large quantities of gas release (oxygen).
- Potential for exothermic hazard

10.2 Chemical stability

- Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

- no data available

10.4 Conditions to avoid

- Contamination
- To avoid thermal decomposition, do not overheat.

10.5 Incompatible materials

- Acids
- Bases
- Metals
- Heavy metal salts
- Powdered metal salts
- Reducing agents
- Organic materials
- Flammable materials

10.6 Hazardous decomposition products

- Oxygen

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Acute oral toxicity**

Acute toxicity estimate : 431 mg/kg - Rat , male and female
Test substance: Hydrogen peroxide
Unpublished reports

Acute inhalation toxicity

LC₅₀ - 4 h (vapour) > 0.17 mg/l - Rat
Test substance: Hydrogen peroxide
No mortality observed at this concentration.
Unpublished reports

Acute dermal toxicity

Acute toxicity estimate 6,440 mg/kg - Rabbit
Test substance: Hydrogen peroxide

	Unpublished reports
Acute toxicity (other routes of administration)	No data available
<u>Skin corrosion/irritation</u>	Causes severe burns.
<u>Serious eye damage/eye irritation</u>	Causes serious eye damage.
<u>Respiratory or skin sensitisation</u>	
hydrogen peroxide	Does not cause skin sensitisation. not sensitising
<u>Mutagenicity</u>	
Genotoxicity in vitro	
hydrogen peroxide	Ames test with and without metabolic activation positive Published data Chromosome aberration test in vitro with and without metabolic activation positive Unpublished reports
Genotoxicity in vivo	
hydrogen peroxide	In vivo micronucleus test - Mouse Oral Method: OECD Test Guideline 474 negative Unpublished reports
<u>Carcinogenicity</u>	
hydrogen peroxide	No data available
<u>Toxicity for reproduction and development</u>	
Toxicity to reproduction/Fertility	
hydrogen peroxide	No toxicity to reproduction
Developmental Toxicity/Teratogenicity	
hydrogen peroxide	No toxicity to reproduction

STOT**STOT - single exposure**

hydrogen peroxide

Exposure routes: Inhalation
 Target Organs: Respiratory Tract
 May cause respiratory irritation.

STOT - repeated exposure

hydrogen peroxide

The substance or mixture is not classified as specific target organ toxicant, repeated exposure according to GHS criteria.

hydrogen peroxide

Inhalation (vapour) 90-day - Rat
 NOAEC: 7 ppm
 Target Organs: Respiratory Tract
 Method: OECD Test Guideline 413
 Unpublished reports

90-day - Rat
 NOAEL: 100 ppm
 Target Organs: Gastrointestinal tract
 Method: OECD Test Guideline 408
 drinking water
 Unpublished reports

Experience with human exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information**12.1 Toxicity****Aquatic Compartment****Acute toxicity to fish**

hydrogen peroxide

LC50 - 96 h : 16.4 mg/l - Pimephales promelas (fathead minnow)
 semi-static test
 Analytical monitoring: yes

Unpublished internal reports
 Harmful to fish.

Acute toxicity to daphnia and other aquatic invertebrates

hydrogen peroxide EC50 - 48 h : 2.4 mg/l - Daphnia pulex (Water flea)
 semi-static test
 Analytical monitoring: yes
 Unpublished internal reports
 Toxic to aquatic invertebrates.

Toxicity to aquatic plants

hydrogen peroxide ErC50 - 72 h : 2.62 mg/l - Skeletonema costatum (marine diatom)
 static test
 Analytical monitoring: yes
 Unpublished internal reports
 Toxic to algae.

Toxicity to microorganisms

hydrogen peroxide EC50 - 0.5 h : 466 mg/l - activated sludge
 static test
 Analytical monitoring: yes
 Method: OECD Test Guideline 209
 Unpublished internal reports

Chronic toxicity to fish

No data available

Chronic toxicity to daphnia and other aquatic invertebrates

hydrogen peroxide NOEC: 0.63 mg/l - 21 Days - Daphnia magna (Water flea)
 flow-through test
 Analytical monitoring: yes
 Published data
 Harmful to aquatic invertebrates with long lasting effects.

12.2 Persistence and degradability**Abiotic degradation**

No data available

Physical- and photo-chemical elimination

No data available

Biodegradation

Biodegradability
 hydrogen peroxide

Ready biodegradability study:
 Method: Degradation in sewage treatment plants
 The substance fulfills the criteria for ultimate aerobic biodegradability and ready biodegradability
 Inoculum: activated sludge
 Unpublished internal reports

Degradability assessment

hydrogen peroxide

The product is considered to be rapidly degradable in the environment

12.3 Bioaccumulative potential**Partition coefficient: n-octanol/water**

hydrogen peroxide

Not potentially bioaccumulable

Bioconcentration factor (BCF)

hydrogen peroxide

Not potentially bioaccumulable

12.4 Mobility in soil**Adsorption potential (Koc)**

hydrogen peroxide

Adsorption/Soil
 Koc: 1.58
 Log Koc: 0.2
 Method: Structure-activity relationship (SAR)
 Unpublished reports

Known distribution to environmental compartments

hydrogen peroxide

Ultimate destination of the product : Water

12.5 Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects**Ecotoxicity assessment****Acute aquatic toxicity**

hydrogen peroxide

Toxic to aquatic life.

Chronic aquatic toxicity

hydrogen peroxide

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product Disposal**

- Limited quantity
- Dilute with plenty of water.
- Flush into sewer with plenty of water.
- Maximum quantity
- Contact manufacturer.
- Contact waste disposal services.
- In accordance with local and national regulations.

Advice on cleaning and disposal of packaging

- Empty containers.
- Clean container with water.
- Dispose of rinse water in accordance with local and national regulations.
- Where possible recycling is preferred to disposal or incineration.
- In accordance with local and national regulations.

SECTION 14: Transport information**ADR**

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class:	8
Label(s):	5.1 (8)
14.4 Packing group	
Packing group	II
Classification Code	OC1
14.5 Environmental hazards	NO
14.6 Special precautions for user	
Tunnel restriction code	(E)
Hazard Identification Number:	58

For personal protection see section 8.

RID

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class:	8
Label(s):	5.1 (8)
14.4 Packing group	
Packing group	II
Classification Code	OC1
14.5 Environmental hazards	NO
14.6 Special precautions for user	

For personal protection see section 8.

IMDG

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class:	8
Label(s):	5.1 (8)
14.4 Packing group	
Packing group	II
14.5 Environmental hazards	NO
Marine pollutant	
14.6 Special precautions for user	
EmS	F-H , S-Q

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

IATA

14.1 UN number	UN 2014
14.2 Proper shipping name	Not permitted for transport
14.3 Transport hazard class	Not permitted for transport
14.4 Packing group	
14.5 Environmental hazards	NO
14.6 Special precautions for user	
Packing instruction (cargo aircraft)	Not permitted for transport
Packing instruction (passenger aircraft)	Not permitted for transport

For personal protection see section 8.

Other information : IATA: permitted under 40%

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Local regulations**

No data available

Notification status

Inventory Information	Status
United States TSCA Inventory	- Listed on Inventory
Canadian Domestic Substances List (DSL)	- Listed on Inventory
Australia Inventory of Chemical Substances (AICS)	- Listed on Inventory
Japan. CSCL - Inventory of Existing and New Chemical Substances	- Listed on Inventory
Korea. Korean Existing Chemicals Inventory (KECI)	- Listed on Inventory
China. Inventory of Existing Chemical Substances in China (IECSC)	- Listed on Inventory
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	- Listed on Inventory
Mexico INSQ (INSQ)	- Listed on Inventory
New Zealand. Inventory of Chemical Substances	- Listed on Inventory
EU. European Registration, Evaluation, Authorisation and Restriction of Chemical (REACH)	- If product is purchased from Solvay in Europe it is in compliance with REACH, if not please contact the supplier.

SECTION 16: Other information**Full text of H-Statements**

- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidizer.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Key or legend to abbreviations and acronyms used in the safety data sheet

- TWA 8-hour, time-weighted average

Further information

- This sheet was updated (refer to the date at the top of this page). Subheadings and text which have been modified since the previous version are indicated with two vertical bars.
- Distribute new edition to clients

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but do not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in any other manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.